GIB HEAD KEYS



Gib Head Keys are available in metric and inch sizes. Metric sizes are made to DIN 6887 / ISO 2492 and Inch sizes are made to BS 46 Part 1. They are made in key steel with a minimum tensile strength of 55KG/mm or stainless (to order).

TO SPECIFY


State the standard, width, height and length Eg DIN 6887 $8 \times 7 \times 50$

GIB HEAD KEYS TO DIN 6887 / ISO 2492 (METRIC)

Taper 1 in 100 Width 'W' Tolerance h9

Height 'H' Measured at Top of Taper

Length 'L' Measured from Tapered End to Under Head



Gib Head Keys, Width 'W'	4	5	6	8	10	12	14	16	18	20	22	25	28	32	36	40	45	50
DIN 6887 (Metric)																		
Height 'H'	4	5	6	7	8	8	9	10	11	12	14	14	16	18	20	22	25	28
Length 'L' As Required																		

GIB HEAD KEYS TO BS 46 PART 1 (IMPERIAL)


Taper 1 in 100

Width 'W' Tolerance up to 5/8" = +0.002" / -0.000"

Tolerance 3/4" to 7/8" = +0.003" / -0.000" Tolerance 1" to 1 1/4" = +0.004" / -0.000" Tolerance over 1 3/8" = +0.005" / -0.000"

Height 'H' Measured at Top of Taper

Length 'L' Overall Length



Gib Head Keys, Width 'W'	1/8	3/16	1/4	1/4	5/16	5/16	3/8	3/8	3/8	7/16	7/16	1/2	1/2	5/8	3/4	7/8	1	1 1/4	1 1/2
BS 46 Part 1 (Imperial)																			
Height 'H'	1/8	3/16	3/16	1/4	1/4	5/16	1/4	5/16	3/8	5/16	7/16	5/16	1/2	5/8	3/4	7/8	1	1 1/4	1 1/2
Length 'L' As Required			•	•••••	•	••••	•••••	•		•••••	• • • • • • • • • • • • • • • • • • • •			•••••	•	***************************************	•	•••••	

^{*} WE MAY BE ABLE TO QUOTE FOR OTHER SIZES NOT SHOWN ABOVE